

Proposed Code Change State Form 41186R

RETURN TO: INDIANA DEPARTMENT OF HOMELAND SECURITY CODE SERVICES SECTION 302 W. Washington Street Room W246

Indianapolis, IN 46204

INSTRUCTIONS:

Only TYPED copy accepted.

(KEY - Dashed line through material to be deleted, underline material to be added)

FOR OFFICE USE ONLY

Received

Code 62.7-09

E3907.2 Damp and wet locations. In damp or wet locations, cabinets and panelboards of the surface type shall be placed or equipped so as to prevent moisture or water from entering and accumulating within the cabinet, and shall be mounted to provide an airspace not less than 1/4 inch (6.4 mm) between the enclosure and the wall or other supporting surface. Cabinets installed in wet locations shall be weatherproof. For enclosures in wet locations, raceways and cables entering above the level of uninsulated live parts shall be installed with fittings listed for wet locations. Exception: Nonmetallic enclosures shall be permitted to be installed without an airspace on a concrete, masonry, tile, or similar surface. REASON AND FISCAL IMPACT This text was extracted from the 2005 Indiana Residential Code. REVIEW RECOMMENDATION Approve Disapprove Approve as amended	Use second sheet for any material re	quiring more space.		
Section number and title	Code Title		Edition	
E3907.2 Exception Proponent Charlie Eidridge Consultant Address 551 Grassy Ln., Indianapolis, IN 46217 PROPOSED CODE CHANGE (Check One) Change to read as follows Add to read as follows Delete and substitute as follows Delete without substitution E3907.2 Damp and wet locations. In damp or wet locations, cabinets and panelboards of the surface type shall be placed or equipped so as to prevent moisture or water from entering and accumulating within the cabinet, and shall be mounted to provide ar airspace not less than 1/4 inch (6.4 mm) between the enclosure and the wall or other supporting surface. Cabinets installed in wet locations shall be weatherproof. For enclosures in wet locations, raceways and cables entering above the level of uninsulated live parts shall be installed with fittings listed for wet locations. Exception: Nonmetallic enclosures shall be permitted to be installed without an airspace on a concrete, masonry, tile, or similar surface. REASON AND FISCAL IMPACT This text was extracted from the 2005 Indiana Residential Code. REVIEW RECOMMENDATION Approve Disapprove Approve as amended	Indiana Residential Code		2009	
Proponent Charlie Eldridge Consultant Address S51 Grassy Ln., Indianapolis, IN 46217 PROPOSED CODE CHANGE (Check One) Change to read as follows Add to read as follows Delete and substitute as follows Delete without substitution E3907.2 Damp and wet locations. In damp or wet locations, cabinets and panelboards of the surface type shall be placed or equipped so as to prevent moisture or water from entering and accumulating within the cabinet, and shall be mounted to provide an airspace not less than 174 inch (6.4 mm) between the enclosure and the wall or other supporting surface. Cacinets installed in wet locations shall be weatherproof. For enclosures in wet locations, raceways and cables entering above the level of uninsulated live parts shall be installed with fittings listed for wet locations. Exception: Nonmetallic enclosures shall be permitted to be installed without an airspace on a concrete, masonry, tile, or similar surface. PREASON AND FISCAL IMPACT This text was extracted from the 2005 Indiana Residential Code. REASON AND FISCAL IMPACT This text was extracted from the 2005 Indiana Residential Code. REVIEW RECOMMENDATION Approve Disapprove Approve as amended	Section number and title		Page	
Charlie Eldridge	E3907.2 Exception		699 & 700	
Address 551 Grassy Ln., Indianapolis, IN 46217 PROPOSED CODE CHANGE (Check One) Change to read as follows Add to read as follows Delete and substitute as follows Delete without substitution B3907.2 Damp and wet locations. In damp or wet locations, cabinets and panelboards of the surface type shall be placed or equipped so as to prevent moisture or water from entering and accumulating within the cabinet, and shall be mounted to provide an airspace not less than 1/4 inch (6.4 mm) between the enclosure and the wall or other supporting surface. Cabinets installed in wet locations hall be weatherproof. For enclosures in wet locations, raceways and cables entering above the level of uninsulated live parts shall be installed with fittings listed for wet locations. Excention: Nonmetallic enclosures shall be permitted to be installed without an airspace on a concrete. masonry, tile, or similar surface. REASON AND FISCAL IMPACT This text was extracted from the 2005 Indiana Residential Code. REVIEW RECOMMENDATION Approve Disapprove Approve as amended	Proponent Title			
Still Grassy Ln., Indianapolis, IN 46217 PROPOSED CODE CHANGE (Check One) Change to read as follows Add to read as follows Delete and substitute as follows Delete without substitution E3907.2 Damp and wet locations. In damp or wet locations, cabinets and panelboards of the surface type shall be placed or equipped so as to prevent moisture or water from entering and accumulating within the cabinet, and shall be mounted to provide ar airspace not less than 1/4 inch (6.4 mm) between the enclosure and the wall or other supporting surface. Cabinets installed in wet locations shall be weatherproof. For enclosures in wet locations, raceways and cables entering above the level of uninsulated live parts shall be installed with fittings listed for wet locations. Exception: Nonmetallic enclosures shall be permitted to be installed without an airspace on a concrete, masonry, tile, or similar surface. REASON AND FISCAL IMPACT This text was extracted from the 2005 Indiana Residential Code. REVIEW RECOMMENDATION Approve Disapprove Approve as amended	Charlie Eldridge Consultant			
PROPOSED CODE CHANGE (Check One) Change to read as follows Add to read as follows Delete and substitute as follows Delete without substitution E3907.2 Damp and wet locations. In damp or wet locations, cabinets and panelboards of the surface type shall be placed or equipped so as to prevent moisture or water from entering and accumulating within the cabinet, and shall be mounted to provide are airspace not less than 1/4 inch (6.4 mm) between the enclosure and the wall or other supporties installed in wet locations shall be weatherproof. For enclosures in wet locations, raceways and cables entering above the level of uninsulated live parts shall be installed with fittings listed for wet locations. Exception: Nonmetallic enclosures shall be permitted to be installed without an airspace on a concrete, masonry, tile, or similar surface. REASON AND FISCAL IMPACT This text was extracted from the 2005 Indiana Residential Code. REASON AND FISCAL IMPACT REVIEW RECOMMENDATION Approve Disapprove Approve as amended	Address		Phone	
Change to read as follows Add to read as follows Delete and substitute as follows Delete without substitution E3907.2 Damp and wet locations. In damp or wet locations, cabinets and panelboards of the surface type shall be placed or equipped so as to prevent moisture or water from entering and accumulating within the cabinet, and shall be mounted to provide ar airspace not less than 1/4 inch (6.4 mm) between the enclosure and the wall or other supporting surface. Cabinets installed in wet locations shall be weatherproof. For enclosures in wet locations, raceways and cables entering above the level of uninsulated live parts shall be installed with fittings listed for wet locations. Exception: Nonmetallic enclosures shall be permitted to be installed without an airspace on a concrete, masonry, tile, or similar surface. REASON AND FISCAL IMPACT This text was extracted from the 2005 Indiana Residential Code. REVIEW RECOMMENDATION Approve Disapprove Approve as amended	551 Grassy Ln., Indianapolis, IN 46217		(317) 370-3444	
E3907.2 Damp and wet locations. In damp or wet locations, cabinets and panelboards of the surface type shall be placed or equipped so as to prevent moisture or water from entering and accumulating within the cabinet, and shall be mounted to provide an airspace not less than 1/4 inch (6.4 mm) between the enclosure and the wall or other supporting surface. Catinets installed in wet locations shall be weatherproof. For enclosures in wet locations, raceways and cables entering above the level of uninsulated live parts shall be installed with fittings listed for wet locations. Exception: Nonmetallic enclosures shall be permitted to be installed without an airspace on a concrete, masonry, tile, or similar surface. REASON AND FISCAL IMPACT This text was extracted from the 2005 Indiana Residential Code. REVIEW RECOMMENDATION Approve Disapprove Approve as amended	PROPOSED CODE CHANGE (Check One)			
equipped so as to prevent moisture or water from entering and accumulating within the cabinet, and shall be mounted to provide an airspace not less than 1/4 inch (6.4 mm) between the enclosure and the wall or other supporting surface. Cabinets installed in wet locations shall be weatherproof. For enclosures in wet locations, raceways and cables entering above the level of uninsulated live parts shall be installed with fittings listed for wet locations. Exception: Nonmetallic enclosures shall be permitted to be installed without an airspace on a concrete, masonry, tile, or similar surface. REASON AND FISCAL IMPACT This text was extracted from the 2005 Indiana Residential Code. REVIEW RECOMMENDATION Approve Disapprove Approve as amended	☐ Change to read as follows ☐ Delete and substitute as follows ☐ Delete without substitution			
This text was extracted from the 2005 Indiana Residential Code. REVIEW RECOMMENDATION Approve Disapprove Approve as amended	airspace not less than 1/4 inch (6.4 mm) between the enclosure and the wall or other supporting surface. Cabinets installed in wet locations shall be weatherproof. For enclosures in wet locations, raceways and cables entering above the level of uninsulated live parts shall be installed with fittings listed for wet locations. Exception: Nonmetallic enclosures shall be permitted to be installed without an airspace on a concrete, masonry, tile, or similar			
This text was extracted from the 2005 Indiana Residential Code. REVIEW RECOMMENDATION Approve Disapprove Approve as amended				
REVIEW RECOMMENDATION Approve Disapprove Approve as amended				
Approve Disapprove Approve as amended	This text was extracted from the 2003 findiana nesidential code.			
Approve Disapprove Approve as amended	REVIEW RECOMMENDATION			
Disapprove Approve as amended				
Approve as amended				
	Further Study			